

L70
25°C 147,000 HoursGlass
BOFGQLED Cone Reflector
Shown with Glare Shield
BOFRLQSoftLED LumaLens
Opal Array LensShown with "S3"
SensorLouvers
BOFLQ

Shown with GFCI

FEATURES

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Internal Ballast Tray for Easy Maintenance. Bollards Can Be Cut to Custom Lengths Upon Request.

Listing & Ratings:

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP65 Sealed LED Compartment.

Finish:

Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

Style:

Clear Prismatic Borosilicate Glass Refractor, Specially Designed Cone Reflector or Internal Louvers

Lens:

Clear UV-Stabilized Polycarbonate Vandal-Resistant Lens or SoftLED LumaLens UV-Stabilized Polycarbonate Opal Vandal-Resistant Lens

Mounting Options:

Mounting Kit with 8 Zinc-Plated Anchor Bolts, Included.

EasyLED LED:

Aluminum Boards

Wattage:

Array: 10w, System: 11.3w; (70w HID Equivalent)
Array: 14.5w, System: 17w; (70w HID Equivalent)
Array: 22w, System: 23.8w; (70w HID Equivalent)

Driver:

Electronic Driver, 120-277V, 50/60Hz or 347V, 50/60Hz (15w Only); Less Than 20% THD and PF>0.90. Standard Internal Surge Protection 2kV. 0-10V Dimming Standard for a Dimming Range of 100% to 10%; Dimming Source Current is 150 Microamps.


Controls:

Fixtures Ordered with Factory-Installed Motion Sensor Controls are Internally Wired for Switching and/or 1-10V Dimming Within the Housing. Remote Direct Wired Interface of 1-10V Dimming is Not Implied and May Not Be Available, Please Consult Factory. Fixtures are Tested with LEPC Controls and May Not Function Properly With Controls Supplied by Others. Fixtures are NOT Designed for Use with Line Voltage Dimmers.

Warranty:

5-Year Warranty for -40°C to +40°C Environment
See Page 2 for Projected Lumen Maintenance Table.

DIMENSIONS



DIMENSIONS

Diameter (D) 7" (178mm)
Height (A) 41 1/2" (1,057mm)

PRODUCT DESCRIPTION

The EasyLED Bollards with choice of optics and lenses are designed to replace HID lighting systems up to 70w MH or HPS. These fixtures are ideal for retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities.

ORDERING INFORMATION

EXAMPLE: BOFRLQF1X22U5KZ36SF



Model	Optics	Wattage	Driver	CCT	Lens	Color	Height	Options
BOFGQ=Round Flat Top Bollard with Glass BOFRLQ=Round Flat Top Bollard with LED Cone Reflector BOFRWQ=Round Flat Top Bollard with White LED Cone Reflector BOFLQ=Round Flat Top Bollard with Louvers	C=Type III* F=Wide Beam Spread *BOFGQ, BOFRLQ and BOFRWQ only	1X10=10w 1X15=15w 1X22=22w	U=120-277V C=347V* *15w Model Only	3K=3000K 4K=4000K 5K=5000K	(Leave Blank)= Clear Lens L=SoftLED LumaLens Opal UV-Stabilized Polycarbonate Array Lens* *Type V White Cone Reflector Only	Z=Bronze B=Black C=Custom (Consult Factory)	(Leave Blank)= 42" Standard Height 36=36" Height 30=30" Height	SF=Single Fuse* DF=Double Fuse* SP=Surge Protection GF1=GFCI Outlet, 15A, 120V GSB=180° Glare Shield, Black GSZ=180° Glare Shield, Bronze GSC=180° Glare Shield, Custom Color (Consult Factory) S3=Microwave Sensor with Dimming & Remote Programming, 120-277V Only. See P17121 Spec. Page for Details. BU=Battery Backup, 90 Minutes* *120-277V Models Only.


ACCESSORIES & REPLACEMENT PARTS




*Shown Mounted

Mounting Accessories (Order Separately, Field Installed)	Accessories (Order Separately, Field Installed)	Replacement Parts (Order Separately, Field Installed)
BOLAN4 Mounting Kit, Includes Bracket & Three (3) 4" Zinc-Plated Anchor Bolts	P17122 Remote Programming Tool for P17121	P17121 Internal Microwave Sensor with Dimming & Remote Programming, 120-277V Only. See P17121 Spec. Page for Details.
BOLAN8 Mounting Kit, Includes Bracket & Three (3) 8" Zinc-Plated Anchor Bolts		BOLPC Replacement Round UV-Stabilized Polycarbonate Vandal-Resistant Lens
BOLAN12 Mounting Kit, Includes Bracket & Three (3) 12" Zinc-Plated Anchor Bolts		BOLPCLL Replacement SoftLED LumaLens Opal UV-Stabilized Polycarbonate Array Lens
BOLAN15 Mounting Kit, Includes Bracket & Three (3) 15" Zinc-Plated Anchor Bolts		BORBASE* Die Cast Base Plate with Powdercoat Finish Over a Chromate Conversion Coating.
BREBASE* Bollard Retrofit Base Kit Adapts New Bollards to Most Existing Bolt Patterns. Fits all LEPG Bollards. Die Cast with Powdercoat Finish, Hardware Included. 11½" Dia. x 1½" H		BOADP1 Adapter Plate with Gaskets for Outlet Boxes. Fits LEPG Round Bollards. Die Cast with Bronze Powdercoat Finish.
*Specify Color: Z=Bronze, B=Black, C=Custom (Consult Factory)		*Specify Color: Z=Bronze, B=Black, C=Custom (Consult Factory)
		For Replacement Battery Backup, see the LEPG LED Battery Backup Specification Sheet.


PHOTOMETRIC DATA

**BOFGQC1X22U5K****Type III**


Grid in feet, Mounting Height = 3 ft.

**BOFLRFQ1X22U5K & BOFRWQF1X22U5K****Type V**

Grid in feet, Mounting Height = 3 ft.

**BOFLQF1X22U5K****Type V**

Grid in feet, Mounting Height = 3 ft.

**BOFRWQF1X22U5KL, LumaLens****Type V**

Grid in feet, Mounting Height = 3 ft.

PHOTOMETRIC PERFORMANCE

Wattage (Catalog Logic)		10W (1X22)	15W (1X15)	20W (1X22)
Input Watts		11.3W	15.9W	23.8W
Optic	CCT	Delivered Lumens		
BOFGQ Glass C=Type III Optic	3000K	787	1,101	1,652
	4000K	853	1,195	1,792
	5000K	889	1,245	1,867
	BUG Rating	B1-U3-G1	B1-U3-G1	B1-U3-G1
BOFGQ Glass F=Type V Optic	3000K	768	1,076	1,613
	4000K	833	1,167	1,750
	5000K	868	1,215	1,823
	BUG Rating	B1-U3-G1	B1-U3-G1	B1-U3-G1
BOFLQ Louvers F=Type V Optic Only	3000K	531	744	1,116
	4000K	576	807	1,211
	5000K	600	841	1,261
	BUG Rating	B0-U2-G0	B1-U2-G1	B1-U3-G1
BOFRLQ & BOFRWQ Cone Reflector C=Type III Optic	3000K	738	1,033	1,549
	4000K	800	1,120	1,680
	5000K	834	1,167	1,750
	BUG Rating	B0-U2-G1	B1-U3-G1	B1-U3-G1
BOFRLQ & BOFRWQ Cone Reflector F=Type V Optic	3000K	1,037	1,452	2,178
	4000K	1,125	1,575	2,362
	5000K	1,172	1,641	2,461
	BUG Rating	B1-U3-G1	B1-U3-G1	B1-U3-G1

PROJECTED LUMEN MAINTENANCE

Data shown for 5000 CCT			Compare to MH			
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated LED Life
L70 Lumen Maintenance @ 25°C / 77°F	All wattages up to and including 24w	1.00	0.95	0.90	0.80	147,000
L70 Lumen Maintenance @ 50°C / 122°F		1.00	0.89	0.78	0.55	67,000
L80 Lumen Maintenance @ 40°C / 104°F		1.00	0.92	0.85	0.70	66,000

NOTES:

1. Projected per IESNA TM-21-11. Data references the extrapolated performance projections for the 116mA base model in a 25°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08.
2. Compare to MH box indicates suggested Light Loss Factor (LLF) to be used when comparing to Metal Halide (MH) systems.