NOTES:





L70 100,000 Hours

Premium Performance Grow Lights


FIXTURE TYPE:

PROJECT:





Dimensions




Order Information Example: LXGL33C3120120 Model Description

LXGL33C3120120 120w 3' COB LED Grow Light
LXGL73C3240120 240w 3' COB LED Grow Light

Specifications and Features:

- Optimum Plant Growth with Higher Yields
- The Color Spectrum is Designed to Promote Photosynthesis:
- Red 77.1% / Blue 22.6% / Green .3%
- Nanometer Ranges: Red 600-699 /Blue 400-499 / Green 500-599
- Cool Operating Temperatures for Easier Ambient Air Temperature
- Dimmable: 0-10V Dimming
- Growing Area Recommended Dimensions:
 120w = 4' Long by 3' Wide
 240w = 6' Long by 4' Wide
- All Aluminum Construction, LED Chips are Potted with High Temperature Silicone Epoxy.
- Lightweight Design for Easy Installation and Re-Location as Desired.
- 10 foot 120V Cord Set Included.
- 5-Year Warranty
- Easy Mount V-Hangers Included
- Electronic Driver, 120-277V, 50/60Hz
- Dimmable Driver
- Operating Temperatures: -35°C to +50°C
- IP67
- CSA: Listed for Wet Locations.












Premium Performance Grow Lights

Photometrics:



Maximum Candels = 1290.876 Located At Horizontal Angle = 90, Vertical Angle = 2.5

#1 - Vertical Plane Through Horizontal Angles (80 - 270) (Through Max. Cd.)

#2 - Horizontal Cone Through Vertical Angle (2.5) (Through Max. Cd.)

GL33C3120120 GL73C3240120

Par Measurements



	12", 18", 24" and 30" Heights
A1 A2 A3	A4 A5 B5 B5
a	CG CG C4

36" M	ounting	Heigh		
A1	A2	АЗ	A4	A5
24	36	42	37	25
B1	B2	B3	B4	B5
28	39	47	40	27
C1	C2	C3	C4	C5
26	34	40	33	22

36" Mounting Height					
A1	A2	A3	A4		
66	90	98	85	61	
B1	B2	B3	B4	B5	
70	98	113	93	63	
C1	C2	C3	C4	C5	
67	91	106	87	58	

24" Mounting Height					
A1	A2	A3	A4	A5	
26	46	58	43	24	
B1	B2	ВЗ	B4	B5	
32	61	78	59	31	
C1	C2	C3	C4	C5	
26	46	56	43	22	

A1	A2	A3	A4	A5
60	106	134	108	66
B1	B2	ВЗ	B4	B5
81	144	186	150	85
C1	C2	C3	C4	C5
65	109	140	113	67

18" Mounting Height					
A1	A2	A3	A4	A5	
20	52	65	49	21	
B1	B2	ВЗ	B4	B5	
34	80	104	75	39	
C1	C2	C3	C4	C5	
23	50	64	47	20	

A1	A2	A3	A4	A5
56	117	141	115	53
B1	B2	ВЗ	B4	B5
84	199	258	190	- 77
C1	C2	C3	C4	C5
67	135	169	127	60

12" Mounting Height				
A1	A2	A3	A4	A5
14	61	73	60	17
B1	B2	B3	B4	85
28	112	136	109	23
C1	C2	C3	C4	C5
16	56	75	59	16

A1	A2	A3	A4	AS
50	130	153	128	76
B1	B2	B3	B4	B5
97	318	409	284	69
C1	C2	СЗ	C4	C5
62	154	210	152	53

Values in µmols/s