



NOTES:

FIXTURE TYPE:

PROJECT:



DESCRIPTION

The AWP Series LED wallpack features adjustable light bars that can be oriented in up, down or up/down orientations to create dramatic lighting effects in any desired area. This family of product is offered with selectable CCT (3000K-4000K-5000K) and the double bar configurations also feature power selectability. Available in two sizes to complement any building exterior and to accommodate multiple mounting heights. The AWP wallpack has efficacies up to 145 LPW to maximize energy savings and utility rebates. This wallpack is ideal for general outdoor lighting, commercial buildings, pathways and sidewalks.

SPECS AT A GLANCE*

Model	AWP-1-25	AWP-2-60	AWP-2-80
Wattage (W)	25W	25W-40W-60W (Switchable)	40W-60W-80W (Switchable)
Lumens (lm)	3139-3286	3139-8392	5076-11,149
Efficacy (LPW)	Up to 145 Lumens per Watt		
Distribution	Type VS		
CCT	3000K-4000K-5000K (Switchable)		
CRI	>70		
Input Voltage	120-277VAC, 50/60Hz		
Operating Temp	-20°C to 40°C (-4°F to 104°F)		
Certifications	UL Listed for Wet Locations, IP65		
Warranty	5 Years		

*Nominal Wattage. Tested at 5000K CCT.

See performance table for more detailed lumen information.

SPECIFICATIONS

CONSTRUCTION

- Precision die-cast aluminum enclosure in a bronze powder-coat finish
- Adjustable light bars can be aimed in any orientation, providing downlighting, uplighting, forward aiming, backlight aiming (AWP-1 and AWP-2), or a combination of up/down/aiming (AWP-2) with a full 360° rotation
- Bars can be locked into desired position using the set screw inside the light bar arm
- Enclosure is supplied with three 1/2" hubs; one on each side and one on the bottom

OPTICS/LEDs

- UV-resistant polycarbonate optical lens
- Type VS distribution
- AWP-1 is offered with one adjustable light bar, 360° rotation, 25W offering up to 3,286 lumens
- AWP-2 is offered with two adjustable light bars, 360° rotation, offered in two configurations;
 - 60W – power selectable (25W-40W-60W) offering between 3139 and 8400 lumens
 - 80W – power selectable (40W-60W-80W) offering between 5076 and 11,200 lumens
- Efficacies up to 145 LPW to maximize energy saving and utility rebates
- All models are CCT selectable between 3000K, 4000K, 5000K, using switch located in the backbox
- L70 >80,000hours
- CRI ≥70

ELECTRICAL

- Class 2 power supply, 120-277VAC, 50/60Hz
- Power supply with high power factor of 90% typical
- Total harmonic distortion of less than 20%

INSTALLATION

- Once light bar angle has been selected, position can be locked into place by securing set screws on the light bar
- Housing mounts to backplate for ease of installation
- Several 1/2" hubs allow surface mount conduit feed
- Mounts to standard 3 1/2" or 4" square electrical J-box

ACCESSORIES

- Button type photocontrol available (PCU) for field installation

TESTING & COMPLIANCE

- UL Listed for Wet Locations, IP65 rated
- Operating temperatures: -20°C to 40°C (-4°F to 104°F)

WARRANTY

- Five year warranty (terms and conditions apply)

ORDERING INFORMATION

EXAMPLE: AWP-2-60-CP-BR



Model	Description
AWP-1-25-C-BR	LED Adjustable Wallpack, 1 Rotatable Bar, 25W, Color Selectable 3000K-4000K-5000K CCT, Bronze Finish
AWP-2-60-CP-BR	LED Adjustable Wallpack, 2 Rotatable Bars, Power Selectable 25W-40W-60W, Color Selectable 3000K-4000K-5000K CCT, Bronze Finish
AWP-2-80-CP-BR	LED Adjustable Wallpack, 2 Rotatable Bars, Power Selectable 40W-60W-80W, Color Selectable 3000K-4000K-5000K CCT, Bronze Finish


Notes

¹ Order as a separate line item; shipped in separate box for field installation


Accessories¹ (Field Installed)

PCU = 120/277VAC Button Photocontrol

DIMENSIONS



AWP-1



AWP-2

PERFORMANCE TABLE

Model	Wattage	CCT	Distribution	Lumen Output	Efficacy
AWP-1-25-C-BR	25W	3000K	TYPE VS	3139	130
	25W	4000K		3282	133
	25W	5000K		3286	134
AWP-2-60-CP-BR	25W	3000K		3139	130
	25W	4000K		3282	133
	25W	5000K		3286	134
	40W	3000K		5076	124
	40W	4000K		5663	143
	40W	5000K		5773	145
	60W	3000K		7270	126
	60W	4000K		8136	139
	60W	5000K		8392	140
AWP-2-80-CP-BR ¹	40W	3000K		5076	124
	40W	4000K		5663	143
	40W	5000K		5773	145
	60W	3000K		7270	126
	60W	4000K		8136	139
	60W	5000K		8392	140
	80W	3000K		9268	110
	80W	4000K		10,964	141
	80W	5000K		11,149	142

¹AWP-2-80 are DLC Standard Qualified

SAMPLE PHOTOMETRICS

AWP-2-60 (60W, 5000K CCT)

IES: TYPE VS

MOUNTING HEIGHT: 10'

TILT: ZERO

