


- Available in LED & GU24
- Wall or Ceiling Mount
- Fade & Rust Resistant Composite Construction with Powder Coated Aluminum Base
- UL Listed for Wet Locations
- Standard Pack QTY: 12


### COMMERCIAL EUROSTYLE



FE361



HCMT: 5 1/4"



EXAMPLE # FE361-LE800C-BFP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
<b>FE361</b>	<b>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b>	<b>W</b> -White <b>B</b> -Black	<b>POLYCARBONATE</b> <b>F</b> -Frosted	<b>P</b> -Photocell
	<b>LE800</b> - 13W, 80 CRI >88 Lumens Per Watt**	<b>W</b> -1140lm 3000K <b>C</b> -1280lm 4000K		
	<b>LE1200</b> - 14W, 80 CRI >102 Lumens Per Watt**	<b>W</b> -1430lm 3000K <b>C</b> -1500lm 4000K		
	<b>LE1800</b> - 22W, 80 CRI >88 Lumens Per Watt**	<b>W</b> -1950lm 3000K <b>C</b> -2130lm 4000K		
	<b>MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR</b>	<b>W</b> -White <b>B</b> -Black	<b>POLYCARBONATE</b> <b>F</b> -Frosted	N/A
	<b>L1800</b> - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**	<b>W</b> -1704lm 3000K <b>C</b> -1824lm 4000K		
	<b>GU24 BASE, 120V</b> <b>G13</b> -1 X 13W <b>G213</b> - 2 X 13W <b>G18</b> -1 X 18W <b>G218</b> - 2 X 18W <b>G26</b> -1 X 27W	<b>W</b> -White <b>B</b> -Black	<b>POLYCARBONATE</b> <b>F</b> -Frosted	<b>P</b> -Photocell <b>L</b> -CFL, 2700K

\*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

\*\*ESTIMATED FROM LED SOURCE

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information, please contact our sales department at (800) 556-7690 or visit [www.ledalux.com](http://www.ledalux.com)