



100W/120W




155W

## PRODUCT DESCRIPTION

Our MHB09 has a high return on investment. The compact and light-weight housing design provides excellent heat management while also supporting three installation methods - hanging, hook, and surface mount. The hanging method does not require additional adapters for installation, making it easy to operate. MHB09 is a versatile high bay suitable for a variety of areas including warehouses, gyms, covered outdoor areas, garden centers, and mezzanines.

## PHOTOMETRICS



## ACCESSORIES



U-Bracket  
Use for surface mount

## SPECIFICATIONS

### Construction

- Casting thermally conducts LED heat to optimize performance and long life.
- With corrosion-resistant powder coating that provides protection and architectural appearance while adapting well to the environment.

### Optics

- Light engines are available in standard 4000K, 5000K( 80 CRI) configurations.
- Scalable Lumen Packages from 11,000 to 17,100 Lumens.
- Anti-UV prismatic translucent len is designed to shape the light uniformity and controls the glare light.

### Electrical

- Universal 120V or 230V/240VAC input voltage.
- PF >90%, THD <20%.
- Operating Temperature Range: -40°C to 40°C (-40 F - + 104 F).

### Mounting

- Hook Mount.
- Conduit Pendant Mount.
- U-Bracket Mount.

### Warranty

- Three-year warranty.

### Certifications

- UL cUL wet location listed.

### Note

• Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C(±5°C) specifications subject to change without notice.

## ORDERING INFORMATION

EXAMPLE: MHB09-100W-120V-50K-B-ML





Model	Wattage	Voltage	CCT	Finish	Lens	Mounting (Option)
MHB09 = High Bay Series	100W 120W 155W	120V	40K = 4000K 50K = 5000K	B = Black	ML = Medium lens	Blank = With Hook Mount TR = Trunnion Mount

## PERFORMANCE DATA

SYSTEM WATTS	PHOTOMETRY	4000K (80CRI)		5000K (80CRI)	
		LUMENS	LPW	LUMENS	LPW
100W	High Bay	11000lm	110 lm/W	11000lm	110 lm/W
120W	High Bay	13000lm	108 lm/W	13000lm	108 lm/W
155W	High Bay	17400lm	112 lm/W	17400lm	112 lm/W

## DIMENSIONS

unit: mm/inch



## MOUNTING



Hook Mount



Conduit Pendant Mount



U-Bracket Mount