



PRODUCT DESCRIPTION

The AMER-VT Series LED vapor tight light is manufactured in the United States and meets BABA (Build America Buy America) requirements. The AMER-VT Series is popular for wet locations and washdown areas. It is designed for pendant mount applications. Optional self-diagnostic emergency driver provides 90-minutes of battery power.

FEATURES

- NEMA 4X Rated
- IP67 Rated
- Fiberglass Housing
- Fully Gasketed
- 0-10V Dimming
- BABA Compliant
- 5-Year Warranty

EXTERNAL SPECIFICATIONS

The housing is constructed from durable fiberglass and is fully gasketed. The clear polycarbonate lens provides superior protection.

DIMENSIONS

51.75" L x 6.8" W x 4.2" D

LED LAMP SPECIFICATIONS

4,000, 6,000, 8,000, and 12,000 lumen output choices. Standard 4000K color temperature and 80 CRI.

ELECTRICAL SPECIFICATIONS

120-277VAC input. 10kV/6kA surge protection.
24W @ 4,000 lumens. 39W @ 6,000 lumens.
51W @ 8,000 lumens. 75W @ 12,000 lumens.

OPERATING TEMPERATURE

-4°F to 131°F for standard model.
41°F to 131°F for model with emergency driver.

CODE COMPLIANCE

CSA Listed to UL Standard for Wet Locations.
NEMA 4X Rated, IP67 Rated, BABA.

WARRANTY

The AMER-VT Series comes with a 5-year factory warranty. Deliberate damage, misuse, or improper installation effectively cancel the warranty.



ORDERING INFORMATION

EXAMPLE: AMER-VT-4000-4-M-C-4K-80-DIM-PM-10KV-BB

Model	Lumens	Length	Distribution	Lens	Color Temp	CRI	Dimming	Mount	Protection	Emergency Driver
AMER-VT	4000 6000 8000 12000	4 (4-feet)	M (medium)	C (clear)	4K (4000K)	80	DIM (0-10V)	PM (pendant)	10KV	BB (10W backup)